

YEI v2 API Documentation

(Document version 2.1.0. Last updated August 4, 2021)

[YEI v2 API Documentation](#)

[User Profiles](#)

[List User Profiles](#)

[Description](#)

[Request Arguments](#)

[Returned Object Properties](#)

[Examples](#)

[Show A User Profile](#)

[Request Arguments](#)

[Returned Object Properties](#)

[Examples](#)

[Create A User Profile](#)

[Description](#)

[Request Properties](#)

[Returned Object Properties](#)

[Examples](#)

[REQUEST](#)

[RESPONSE](#)

[Update A User Profile](#)

[Description](#)

[Request Properties](#)

[Returned Object Properties](#)

[\(see User Profile Show\)](#)

[Examples](#)

[Archive A User Profile](#)

[Description](#)

[Returned Object Properties](#)

[Examples](#)

[Forgot Password](#)

[Posts](#)

List Posts

[Description](#)

[Request Arguments](#)

[Returned Object Properties](#)

[Examples](#)

[REQUEST](#)

[RESPONSE \(truncated\)](#)

Show a Post

[Description](#)

[Request Arguments](#)

[Returned Object Properties](#)

[Examples](#)

[REQUEST](#)

[RESPONSE](#)

Send Recognition (create a post)

[Description](#)

[Request Arguments](#)

[Returned Object Properties](#)

[Examples](#)

[REQUEST](#)

[RESPONSE](#)

Rewards

List Rewards

[Description](#)

[Request Arguments](#)

[Returned Object Properties](#)

[Examples](#)

[REQUEST](#)

[RESPONSE \(truncated\)](#)

Show a Reward

[Description](#)

[Returned Object Properties](#)

[Examples](#)

Redeem a Reward

[Description](#)

[Request Arguments \(optional\)](#)

[Request Arguments \(required for Behavior Bonuses\)](#)

[Returned Object Properties](#)

[Examples](#)

[REQUEST](#)
[RESPONSE](#)

[Redemptions](#)

[Index](#)

[Description](#)
[Returned Object Properties](#)
[Examples](#)

[Process Redemption](#)

[Description](#)
[Request Arguments](#)
[Returned Object Properties](#)
[Examples](#)

[REQUEST](#)
[RESPONSE](#)
[REQUEST](#)
[RESPONSE](#)

[Tags](#)

[List of Preferred Tags](#)

[Description](#)
[Returned Object Properties](#)
[Examples](#)

[Comments](#)

[Description](#)
[Returned Object Properties](#)
[Examples](#)

[Comment Create](#)

[Description](#)
[Request Arguments](#)
[Returned Object Properties](#)
[Examples](#)

[REQUEST](#)
[RESPONSE](#)

[Comment Update](#)

[Description](#)
[Request Arguments](#)
[Returned Object Properties](#)
[Examples](#)

[REQUEST](#)
[RESPONSE](#)

[Comment Delete](#)[Description](#)[Request Arguments](#)[Returned Object Properties](#)[Examples](#)[REQUEST](#)[RESPONSE](#)[Following](#)[Description](#)[Returned Object Properties](#)[Examples](#)[Notifications](#)[Index](#)[Description](#)[Returned Object Properties](#)[Examples](#)[REQUEST](#)[RESPONSE \(truncated\)](#)[Dismiss](#)[Description](#)[Examples](#)[REQUEST](#)[Clear](#)[Description](#)[Examples](#)[REQUEST](#)[Stats](#)[Description](#)[Returned Object Properties](#)[Examples](#)[Push Notifications \(Parse.com\)](#)[Register](#)[Description](#)[Request Arguments](#)[Examples](#)[REQUEST](#)[Sample Endpoints for mobile](#)

User_Profiles

List User Profiles

GET

Description

Returns an array of user_profiles

Request Arguments

- page : Integer (optional)
- per_page : Integer (optional)
- filter : String (optional)
 - 'active' (default)
 - 'inactive'
 - 'deleted'
 - 'all'
- email: string (optional)
 - email address (supports partial match)
-
- search : string (optional) string
 - find by first and/or last name (with partial matches)
- paged : boolean (optional)
 - if passed, results will be wrapped as a paged response

Returned Object Properties

*In this case the response body will be an **Array of Objects**, each object will have these properties:*

key	data type	notes
-----	-----------	-------

id	string	
created_at	string	ISO 8601 full time format
first_name	string	
last_name	string	
status	string	'active', 'inactive', 'terminated'
profile_email	string	Email for this profile for notifications.
login_email	string	Email to use as login id
profile_pic	string	full url
profile_pic_small	string	full url
dob_day	integer	less than 31
dob_month	integer	less than 12
start_date	string	'YYYY-MM-DD'
termination_date	string	'YYYY-MM-DD'
reference	string	can be used to hold custom info, such as employee ID.
groups	array	of objects
following	array	array of user_profile ids this user_profile is following.
followers	array	array of user_profile ids who are following this user_profile
roles	array	array of string of roles ("user" and "admin")
tags	array	array of tags from all posts in which the user was a recipient, along with counts for the number of posts associated with a given tag
last_login	string	ISO 8601 time format of last login date
shipping_address	object	user preference stored for shipping address

giving_account	object	
redemption_account	object	

Giving Account and Redemption account objects will both have the following properties

balance	integer	
currency	string	default is "points"
conversion_rate	integer	default is 1

Groups array will contain objects with these properties

id	integer	
name	string	
description	string	

Examples

REQUEST

```
GET api/2/user_profiles
```

RESPONSE (truncated)

```
[
  {
    "id": "52e9e2eb549d52e7a1000055",
    "first_name": "Test",
    "last_name": "User",
    "profile_email": "test@youearnedit.com",
    "login_email": "test@youearnedit.com",
    "created_at": "2014-01-29T23:30:39-06:00",
    "profile_pic":
    "https://yei-production-images.s3.amazonaws.com/uploads/user_profile/
    image/52e9e37f549d52e7a10000cb/medium_130305597728081127.jpg",
```

```

    "profile_pic_small":
    "https://yei-production-images.s3.amazonaws.com/uploads/user_profile/
    image/52e9e37f549d52e7a10000cb/small_130305597728081127.jpg",
    "dob_day": null,
    "dob_month": null,
    "start_date": null,
    "termination_date": null,
    "job_title": null,
    "about": "this is a blurb about the user",
    "status": "active",
    "active": true,
    "last_login": "2014-04-01T08:42:37-05:00",
    "reference": null,
    "shipping_address": null,
    "groups": [
    {
        id: "533460346c7db96d8800031e",
        name: "Engineering Team",
        description: "The folks who create happiness"
    }
    ],
    "following":
    [
        "52e9e35b549d52e7a10000b2",
        "52e9e387549d52e7a10000d0"
    ],
    "followers":
    [
        "52e9e2eb549d52e7a1000067",
        "52e9e33e549d52e7a100009e",
        "52e9e346549d52e7a10000a3",
        "52e9e377549d52e7a10000c6",
        "52e9e387549d52e7a10000d0",
        "533d6cc3cdad828815000007",
        "534464f7cdad828081000008",
        "534ecbdfcdad8222a9000007"
    ],
    "tags":
    [
        {
            id: "52e9e22f549d52e7a100000f",
            name: "Create Happiness",
            count: 6,

```

```
    type: "PreferredTag"
  },
  {
    id: "52e9e22f549d52e7a100000c",
    name: "Eyes on the Prize",
    count: 6,
    type: "PreferredTag"
  },
  {
    id: "52e9e22f549d52e7a100000b",
    name: "Leave it Better",
    count: 3,
    type: "PreferredTag"
  },
  {
    id: "52e9e22f549d52e7a100000e",
    name: "Adapt or Die",
    count: 2,
    type: "PreferredTag"
  }
],
  "giving_account": {
    "balance": 6240,
    "currency": "points",
    "conversion_rate": 1
  },
  "redemption_account": {
    "balance": 30625,
    "currency": "points",
    "conversion_rate": 1
  },
},
{...}
]
```

Show A User Profile

GET /api/2/user_profiles/{USER_PROFILE_ID}

GET /api/2/user_profiles/me (for Oauth associated user only)

Description

This request returns an object with a single user_profile key whose value is an object

Request Arguments

user_profile_id	required (unless request is sent to /me and Oauth)
-----------------	---

Returned Object Properties

key	data type	notes
id	string	
first_name	string	
last_name	string	
status	string	'active', 'inactive', 'terminated'
profile_email	string	
login_email	string	
profile_pic	string	full url
profile_pic_small	string	full url
dob_day	integer	less than 31
dob_month	integer	less than 12

start_date	string	'YYYY-MM-DD'
termination_date	string	'YYYY-MM-DD'
groups	array	of objects
following	array	array of user_profile ids this user is following.
roles	array	array of string of roles ("user" and "admin")
giving_account	object	
redemption_account	object	

Giving Account and Redemption account objects will both have the following properties

balance	integer	
currency	string	default is "points"
conversion_rate	integer	default is 1

IF the User/Profile belongs to any groups, Each element in the Groups Array will be an object with the following properties

id	string	the group id
name	string	
description	string	

Examples

REQUEST

```
GET /api/2/user_profiles/52e9e377549d52e7a1000055
```

RESPONSE

```

    {
"user_profile": {
  "id": "52e9e377549d52e7a1000055",
  "first_name": "Test",
  "last_name": "User",
  "profile_email": "test@youearnedit.com",
  "login_email": "otheremail@youearnedit.com",
  "status": "active",
  "dob_day": null,
  "dob_month": null,
  "start_date": null
  "termination_date": null,
  "reference": null,
  "profile_pic":
"https://yei-production-images.s3.amazonaws.com/uploads/user_profile/
image/52e9e377549d52e7a1000055/medium_130335881910511799.jpg",
  "profile_pic_small":
"https://yei-production-images.s3.amazonaws.com/uploads/user_profile/
image/52e9e377549d52e7a1000055/small_130335881910511799.jpg",
  "groups": [

    {
      id: "533460346c7db96d8800031e",
      name: "Engineering Team",
      description: "The folks who create happiness"
    }
  ],
"roles":
  [
    "user",
    "admin"
  ],
"following": [
    "52e9e35b549d52e7a10000b2",
    "52e9e387549d52e7a10000d0"

```

```
],
"followers":
[
  "52e9e2eb549d52e7a1000067",
  "52e9e33e549d52e7a100009e",
  "52e9e346549d52e7a10000a3",
  "52e9e377549d52e7a10000c6",
  "52e9e387549d52e7a10000d0",
  "533d6cc3cdad828815000007",
  "534464f7cdad828081000008",
  "534ecbdfcdad8222a9000007"
],
"tags":
[
  {
    id: "52e9e22f549d52e7a100000f",
    name: "Create Happiness",
    count: 6,
    type: "PreferredTag"
  },
  {
    id: "52e9e22f549d52e7a100000c",
    name: "Eyes on the Prize",
    count: 6,
    type: "PreferredTag"
  },
  {
    id: "52e9e22f549d52e7a100000b",
    name: "Leave it Better",
    count: 3,
    type: "PreferredTag"
  },
  {
    id: "52e9e22f549d52e7a100000e",
    name: "Adapt or Die",
    count: 2,
    type: "PreferredTag"
  }
],
"giving_account": {
  "balance": 2939,
```

```

        "currency": "points",
        "conversion_rate": 1
    },
    "redemption_account": {
        "balance": 3451,
        "currency": "points",
        "conversion_rate": 1
    }
}
}

```

Create A User Profile

POST /api/2/user_profiles

Description

Create a new user_profile and associated user

Request Properties

	key	value	notes
	user_profile	object	

The user_profile object will have the following properties

login_email	string	required
first_name	string	required
last_name	string	required

profile_email	string	optional (profile email set to login_email if blank)
username	string	optional
password	string	optional
dob_day	integer	optional; must be less than 31
dob_month	integer	optional; must be less than 12
start_date	string	optional; must be "YYYY-MM-DD"
termination_date	string	optional; must be "YYYY-MM-DD"
status	string	optional; default: 'active', can be 'active', 'inactive', 'terminated'
redemption_points	integer	optional; defaults to company default, or 0 if that is blank
giving_points	integer	optional; defaults to company default, or 0 if that is blank
reference	string	used for employer assigned id or other misc data
group_names	array	optional: Array of Strings, each string must match an existing group name exactly
report_to	string	optional; the ID of the User Profile belonging to this user's manager

Returned Object Properties

key	data type	notes
user_profile	object	

`user_profile` object has these properties

id	string	
----	--------	--

first_name	string	
last_name	string	
profile_email	string	
login_email	string	
dob_day	integer	
dob_month	integer	
start_date	string	“YYYY-MM-DD”
termination_date	string	“YYYY-MM-DD”
status	string	
profile_pic	string	null if no url
profile_pic_small	string	null if no url
groups	array	
giving_account	object	
redemption_account	object	
reference	string	

Giving Account and Redemption account objects will both have the following properties

balance	integer	
currency	string	default is “points”
conversion_rate	integer	default is 1

Examples

REQUEST

```
POST /api/2/user_profiles
{
  "user_profile": {
```

```
    "login_email": "test@example.com",
    "profile_email": "jason@example.com",
    "first_name": "test",
    "last_name": "user",
    "username": "test.user",
    "password": "userpassword",
    "status": "active",
    "group_names": ["API Test", "Austin"]
  }
}
```

RESPONSE

```
{
  "user_profile": {
    "id": "52e9e377549d52e7a1000055",
    "first_name": "Test",
    "last_name": "User",
    "profile_email": "jasonexample.com",
    "login_email": "test@example.com",
    "dob_day": null,
    "dob_month": null,
    "start_date": null,
    "termination_date": null,
    "status": "active",
    "profile_pic":
      "https://yei-production-images.s3.amazonaws.com/uploads/user_profile/
      image/52e9e377549d52e7a1000055/medium_130335881910511799.jpg",
```

```
    "profile_pic_small":  
    "https://yei-production-images.s3.amazonaws.com/uploads/user_profile/  
image/52e9e377549d52e7a1000055/small_130335881910511799.jpg",  
    "groups": [  
      {  
        id: "533d46c7db96d00031edfdfd",  
        name: "API test",  
        description: "Testing the API"  
      },  
      {  
        id: "353d46c96d0007db31edfdfd",  
        name: "Austin",  
        description: "The people in this great city"  
      },  
    ],  
    "roles":  
    [  
      "user",  
      "admin"  
    ],  
    "giving_account": {  
      "balance": 6000,  
      "currency": "points",  
      "conversion_rate": 1  
    },  
    "redemption_account": {  
      "balance": 0,  
      "currency": "points",  
      "conversion_rate": 1  
    }  
  }  
}
```

Update A User Profile

PUT /api/2/user_profiles/{USER_PROFILE_ID}

Description

Update a user_profile response will be the same as calling user profile show if successful

Request Properties

key	value	notes
user_profile	object	

The user_profile object will have the following properties

login_email	string	optional
profile_email	string	optional
first_name	string	optional
last_name	string	optional
username	string	optional
password	string	optional
status	string	(optional) "active", "inactive", "terminated"
group_names	array	(optional) an array of strings matching group names, empty array ignored unless literal_groups is true
literal_groups	boolean	(optional) if true, treats group_names literally, meaning null or [] would result in the profile being removed from all groups

reference	string	optional
dob_day	integer	
dob_month	integer	
start_date	string	"YYYY-MM-DD"
termination_date	string	"YYYY-MM-DD"
redemption_points	integer	optional
giving_points	integer	optional
report_to	string	(optional) the ID of the User Profile belonging to this user's manager

Returned Object Properties

(see [User Profile Show](#))

Examples

REQUEST

```
PUT /api/2/user_profiles/52e9e377549d52e7a1000055
{
  "user_profile": {
    "profile_email": "test@example.com",
    "status": "inactive",
    "dob_day": 18,
    "dob_month" : 10
  }
}
```

RESPONSE

```
{
"user_profile": {
  "id": "52e9e377549d52e7a1000055",
  "first_name": "Test",
  "last_name": "User",
  "email": "test@example.com",
  "status": "inactive",
  "dob_day": 18,
  "dob_month" : 10,
  "start_date": "2010-10-22",
  "termination_date": null,
  "profile_pic":
"https://yei-production-images.s3.amazonaws.com/uploads/user_profile/
image/52e9e377549d52e7a1000055/medium_130335881910511799.jpg",
  "profile_pic_small":
"https://yei-production-images.s3.amazonaws.com/uploads/user_profile/
image/52e9e377549d52e7a1000055/small_130335881910511799.jpg",
  "groups": [],
  "giving_account": {
    "balance": 6000,
    "currency": "points",
    "conversion_rate": 1
  },
  "redemption_account": {
    "balance": 0,
    "currency": "points",
    "conversion_rate": 1
  }
},
},
```

```
"reference": null,  
}
```

Archive A User Profile

```
DELETE /api/2/user_profiles/{USER_PROFILE_ID}
```

Description

Archive a User Profile*

Returned Object Properties

empty

Examples

REQUEST

```
DELETE /api/2/user_profiles/52e9e377549d52e7a1000055
```

RESPONSE

200 OK

Forgot Password

You can use a web view to display the page at

GET /users/password/new

or submit the users email address to:

POST /users/password?user[email]={useremail}

Posts

List Posts

GET api/2/posts

Description

Returns an Array of Post Object.

Important returns a 'page' of posts (default 10 posts)

Request Arguments

Takes the following as query strings

property	notes (ALL Optional)
page	(optional) defaults to 1
paged	(optional) if passed, results will be wrapped as a paged response
per_page	(optional) page size, defaults to 10
filter	(optional) defaults to 'all', can be: 'recognition', 'redemptions', 'following'
user_profile	(optional) the id of a single user profile for whom you want to see posts
tag	(optional, requires user_profile) the id of a company tag (used in conjunction with user_profile, returns only those posts that are tagged with the tag id).
group	(optional) group ids

search_text	(optional) <code>first_name</code> or <code>last_name</code> of user (can be partial match) e.g., "jo" will return all posts where to or from any user whose first or last name contains 'jo' such as joe, joseph, john, jon, etc
sort_by	(optional) must be: 'date', (requires <code>sort_dir</code>)
sort_dir	(requires <code>sort_by</code>) , can be: <code>asc</code> (for ascending) default is <code>desc</code>

Returned Object Properties

Returns an Array, with each element being an object with the following properties

key	value	notes
<code>id</code>	string	
<code>points</code>	integer	
<code>type</code>	string	
<code>message</code>	string	
<code>hidden</code>	boolean	
<code>private</code>	boolean	
<code>from</code>	object	see <code>user_profile Show</code> for properties
<code>to</code>	object	see <code>user_profile Show</code> for properties
<code>comments</code>	array	see <code>Comments Index</code>

Examples

REQUEST

```
GET api/2/posts
```

RESPONSE (truncated)

```
[
  {
    "id": "5329c905ad7256e2d1000003",
    "points": 2,
    "type": "recognition",
    "message": "ola",
    "hidden": false,
    "private": false,
    "from": {
      "id": "52e9e230549d52e7a1000013",
      "first_name": "yei",
      "last_name": "Admin",
      "profile_email": "test@youearnedit.com",
      "login_email": "test@youearnedit.com",
      "status": "active",
      "dob_day": null,
      "dob_month": null,
      "start_date": null,
      "termination_date": null,
      "reference_id": null,
      "profile_pic": null,
      "profile_pic_small": null,
      "groups": [],
      "giving_account": {
        "balance": 94,
        "currency": "points",
        "conversion_rate": 1
      },
      "redemption_account": {
        "balance": 0,
        "currency": "points",
        "conversion_rate": 1
      }
    }
  }
]
```

```

},
"to": [
  {
    "id": "52e9e387549d52e7a10000d0",
    "first_name": "Tara",
    "last_name": "Sinclair",
    "profile_email": tara.sinclair@youearnedit.com",
    "login_email": tara.sinclair@youearnedit.com",
    "status": "active",
    "dob_day": null,
    "dob_month": null,
    "start_date": null
    "termination_date": null,
    "reference_id": null,
    "profile_pic":
"https://yei-production-images.s3.amazonaws.com/uploads/user_profile/
image/52e9e387549d52e7a10000d0/medium_130293703467717799.JPG",
    "profile_pic_small":
"https://yei-production-images.s3.amazonaws.com/uploads/user_profile/
image/52e9e387549d52e7a10000d0/small_130293703467717799.JPG",
    "groups": [],
    "giving_account": {
      "balance": 1710,
      "currency": "points",
      "conversion_rate": 1
    },
    "redemption_account": {
      "balance": 5781,
      "currency": "points",
      "conversion_rate": 1
    }
  }
],
"comments": []

```

```

    },
    {...}
]

```

Show a Post

GET `api/2/posts/{POST_ID}`

Description

Returns an individual Post

Request Arguments

none

Returned Object Properties

Returns an object with 1 key 'post', whose value is an Object with the following properties

key	value	notes
id	string	
points	integer	
type	string	
message	string	
hidden	boolean	
private	boolean	
from	object	see user_profile Show for properties
to	object	see user_profile Show for properties
comments	array	see Comments Index

Examples

REQUEST

```
/api/2/posts/5329c905ad7256e2d1000003
```

RESPONSE

```
{  
  
  post:  
  {  
  
    id: "522334966c7db9461800000a",  
    points: 50,  
    type: "recognition",  
    message: "Ummm thanks for TOTALLY saving the day.",  
    hidden: false,  
    private: false,  
    from:  
    {  
  
      id: "5222e362549d52e7a10000ad",  
      first_name: "Jessa",  
      last_name: "Groff",  
      profile_email: "test@youearnedit.com",  
      "login_email": "tara.sinclair@youearnedit.com",  
      "status": "active",  
      "dob_day": null,  
      "dob_month": null,  
      "start_date": null,  
      "termination_date": null,  
      "reference_id": null,  
      profile_pic:  
      "https://yei-production-images.s3.amazonaws.com/uploa
```

```

ds/user_profile/image/52e9e352549d52e7a10000ad/medium_
_130318553880180178.png",
  profile_pic_small:
"https://yei-production-images.s3.amazonaws.com/uploa
ds/user_profile/image/52e9e352549d52e7a10000ad/small_
130318553880180178.png",
  groups: [ ],
  giving_account: {},
  redemption_account: {}
},
to:
[
  {
    id: "5222e3be542d52e7a10000fd",
    first_name: "Kim",
    last_name: "Lowery",
    profile_email: "test@youearnedit.com",
    login_email: "test@youearnedit.com",
    "status": "active",
    "dob_day": null,
    "dob_month": null,
    "start_date": null
    "termination_date": null,
    "reference_id": null,

    profile_pic:
      "https://yei-production-images.s3.
amazonaws.com/uploads/user_profile
/image/52e9e3be549d52e7a10000fd/me
dium_130354119496204709.jpg",
    profile_pic_small:
      "https://yei-production-images.s3.
amazonaws.com/uploads/user_profile

```

```

        /image/52e9e3be549d52e7a10000fd/sm
        all_130354119496204709.jpg",
        groups: [ ],
        giving_account:
        {
            balance: 7850,
            currency: "points",
            conversion_rate: 1
        },
        redemption_account:
        {
            balance: 5773,
            currency: "points",
            conversion_rate: 1
        }
    },
    comments: [ ]
}
}

```

Send Recognition (create a post)

POST `api/2/recognition`

Description

Send recognition and points to a user.

NOTE: This method only makes sense in the context of an OAuth based session (ie, a logged in user). If Basic Auth is used to make this call, then the company “API” user will be used (and since the API user has no sending or redemption balance, the call will fail).

Request Arguments

key	value	notes
recognition	object	wrapper for all other properties

key	value	notes
points	integer	
message	string	
visibility	boolean	
tag	string	
user_tag	string	
to	array	user_profile ids

Returned Object Properties

Examples

REQUEST

POST api/2/recognition

```
{
  "recognition": {
    "points": 100,
    "message": "Thanks!",
    "visibility": true,
```

```
"tag": "PreferredTag",
"user_tag": "Tag",
"to": [
  "5222e2eb549d52e7a1000067"
]
}
```

RESPONSE

200 OK

Rewards

List Rewards

GET `api/2/rewards`

Description

Returns an Array of reward objects

Request Arguments

property	type	notes
page	integer	defaults to 1

paged	boolean	(optional) - if passed, results will be wrapped as a paged response
per_page	integer	(optional) defaults to 12
sort	string	(optional) defaults to 'points', can be: 'alpha'
category_id	string	(optional) id of category to filter on
search	string	(optional) looks at the item's name field for fuzzy matches

Returned Object Properties

For the Returned Array each element will be an object with these properties

key	value	notes
id	string	id of the item to be redeemed
name	string	
description	string	
image_url	string	2048 x 1152 image url
image_medium_url	string	355 x 200 image url
image_small_url	string	62 x 35 image url
categories	array	elements are objects (see category below)

CATEGORY OBJECT PROPERTIES

key	value	notes
id	string	id of the category
name	string	name of category
description	string	

Examples

REQUEST

```
GET api/2/rewards
```

RESPONSE (truncated)

```
[
  {
    "id": "52e9e29d549d52e7a1000046",
    "name": "Buy points to Award",
    "points": 500,
    "description": "It's amazing how quickly these Recognition
Points go! And, you still have some co-workers you want to show some
love. Fear not! You can recycle the love and buy some Recognition
Points.",
    "image_url":
"https://yei-production-images.s3.amazonaws.com/uploads/item/image/52
e9e29d549d52e7a1000046/130277458885070650.jpg"
  },
  {...}
]
```

Show a Reward

```
GET api/2/rewards/:reward_id
```

Description

Returns an Object with one key 'item'

Returned Object Properties

For the returned object the value of the key 'item' will be an object with these properties

key	value	notes
id	string	id of the item to be redeemed
name	string	
description	string	
image_url	string	
categories	array	elements are objects (see category below)
kind	string	pooling, behavior_bonus, give_back, reward

Fields Included when kind is behavior_bonus

documentation_required	boolean	
documentation_label	string	
times_redeemed	integer	
required_proof	string	explanation of what proof the redeemer must provide for redemption to be accepted
redemption_time_frame	string	how frequently the item can be redeemed for options are [day, week, month, quarter, life_time, unlimited]

CATEGORY OBJECT PROPERTIES

key	value	notes
id	string	id of the category
name	string	name of category
description	string	

Examples

REQUEST

```
GET api/2/rewards/52e9e29d549d52e7a1000046
```

RESPONSE

```
{
  "item": {
    "id": "52e9e29d549d52e7a1000046",
    "name": "Buy points to Award",
    "points": 500,
    "description": "It's amazing how quickly these Recognition Points go! And, you still have some co-workers you want to show some love. Fear not! You can recycle the love and buy some Recognition Points.",
    "image_url":
    "https://yei-production-images.s3.amazonaws.com/uploads/item/image/52e9e29d549d52e7a1000046/130277458885070650.jpg"
  }
}
```

Redeem a Reward

```
POST api/2/rewards/:item_id/redeem
```

Description

Redeem a reward for a user

NOTE: This method only makes sense in the context of an OAuth based session (ie, a logged in user). If Basic Auth is used to make this call, then the company “API” user will be used (and since the API user has no sending or redemption balance, the call will fail).

Request Arguments (optional)

param	type	notes
address_type	string	‘custom’, ‘profile’, or ‘company’ company - use company address for shipping profile - use user profile address for shipping custom - user values from ‘address’ param for shipping
address	object	properties: { street_1, type: String street_2, type: String city, type: String zip, type: String state, type: String country, type: String }

Request Arguments (required for Behavior Bonuses)

param	type	notes
behavior_bonus_url	string	<ul style="list-style-type: none"> required if documentation_required is true and behavior_bonus_file is not provided link to the proof that the person did the action
behavior_bonus_file		<ul style="list-style-type: none"> required if documentation_required is true and behavior_bonus_url is not provided link to the proof that the person did the action
reward	object	object with one property :behavior_bonus_comment which should be a user provided string

note rewards are synonymous with items in this context

Returned Object Properties

key	value	notes
result	string	returns name and points if success, else that there was a problem

Examples

REQUEST

```
POST api/2/rewards/52e9e29d549d52e7a1000046/redeem
```

RESPONSE

```
{"result": "Buy points to Award redeemed for 500 points"}
```

Redemptions

Index

```
GET api/2/redemptions
```

Description

Returns an Array of pending item orders

property	notes
status	defaults to 'pending', can be; 'approved', 'paid', 'ordered', 'shipped', 'delivered'
user_profile	(optional) id - filter all redemptions down to the user_profile id
page	(optional) all responses are paged, default is 1

paged	(optional) if passed, results will be wrapped as a paged response
per_page	(optional) defaults to 12
search_text	searches user first and last names, and item names
sort_by	defaults to 'date', can be 'redeemer', 'reward_name', 'points'
sort_dir	defaults to 'desc' can be: 'asc' (for ascending)

Returned Object Properties

Returned Array will consist of item_order objects with the following props

key	value	notes
id	string	id of the item_order
status	string	'pending' by default
status_message	string	often but not always null
extra	object	set of properties with extra information about the order (item dependent)
fulfillment_details	object	set of properties with extra information about the fulfillment (item dependent)
item	object	see Show a Reward
user_profile	object	see User Profile show

Examples

REQUEST

```
GET api/2/redemptions
```

RESPONSE

```
[
```

```
{
  id: "5344c8b3d00fb93a3d000003",
  status: "pending",
  status_message: null,
  extra:
  {
    first_name: "Mike",
    last_name: "McCown",
    points: 1000,
    store_id: "14837",
    cost: 1050,
    item_name: "$10 Donors Choose Gift Code"
  },
  fulfillment_details:
  {
    updated_at: "2014-05-06T23:55:06-05:00",
    number: "R734440650",
    state: "cart",
    fulfillment_code: "5Z7JRF77Z",
    fulfillment_exp: "2014-11-07",
    fulfillment_id: "",
    fulfillment_pin: null,
    fulfillment_url:
    "http://www.donorschoose.org/redeem?code=5Z7JRF77Z",
    last_response: null
  },

  item:
  {
    id: "52e9e29d549d52e7a1000046",
    name: "Buy points to Award",
    points: 500,
  }
}
```

```
description: "It's amazing how quickly
these Recognition Points go! And, you still
have some co-workers you want to show some
love. Fear not! You can recycle the love
and buy some Recognition Points.",
image_url:
"https://vei-production-images.s3.amazonaws
.com/uploads/item/image/52e9e29d549d52e7a10
00046/130277458885070650.jpg",
categories:
[
  {
    id:
      "52e990ba549d52acab00007c"
    ,
    name: "Experiences",
    description: null
  }
]
},
user_profile:
{
  id: "52e9e2eb543e52e7a1000067",
  first_name: "Mike",
  last_name: "McCown",
  profile_email: "test@youearnedit.com",
  "login_email": "otheremail@youearnedit.com",
  "status": "active",
  "dob_day": null,
  "dob_month": null,
  "start_date": null
  "termination_date": null,
  "reference_id": null,
```

```
    profile_pic:
      "https://vei-production-images.s3.amazonaws.com/uploads/user\_profile/image/52e9e2eb549d52e7a1000067/medium\_130293717068457464.jpg"
    ,
    profile_pic_small:
      "https://vei-production-images.s3.amazonaws.com/uploads/user\_profile/image/52e9e2eb549d52e7a1000067/small\_130293717068457464.jpg"
    ,
    giving_account:
      {
        balance: 11685,
        currency: "points",
        conversion_rate: 1
      },
    redemption_account:
      {
        balance: 25757,
        currency: "points",
        conversion_rate: 1
      },
    groups:
      [
        {
          id:
            "533460346c7db96d8800031e"
          ,
          name: "Engineering Team",
          description: "The folks
            who create happiness"
        }
      ]
  }
}
```

```

    }
  ]

```

Process Redemption

POST `api/2/process_redemption/:status(/:id)`

Description

Request Arguments

Property	Notes
id	item_order id (optional. If not given set ids key in post body)
status	REQUIRED the state the order should move to, eg 'approve', 'deny', 'cancel', 'complete'

message	string	required if status is 'deny' (give a reason why)
ids	array of strings	required if no id is passed

Returned Object Properties

key	value	notes
msg	Array of Arrays	inner Array has 2 string type elements

Examples

REQUEST

POST `process_redemption/approve/530520e56c7db957cc00000a`

RESPONSE

```
{
  "msg": [
    [
      "notice",
      "Order approved."
    ]
  ]
}
```

REQUEST

```
POST process_redemption/cancel/530520e56c7db957cc00000a
```

RESPONSE

```
{
  "msg": [
    [
      "notice",
      "Order canceled."
    ]
  ]
}
```

Tags

List of Preferred Tags

GET `api/2/tags`

Description

Returns an Array of preferred tags

Returned Object Properties

key	value	notes
id	string	id of the tag
name	string	
description	string	

Examples

REQUEST

GET `api/2/tags`

RESPONSE (truncated)

```
[
  {
    tag:
      {
        id: 52e9456d549d52e7a1000046,
        name: "Open Book",
```

```

        description: "Don't be stubborn: ask for
        directions. Be willing to listen to the
        feedback and opinions of others. You might
        learn something. Ask lots of questions.
        Don't hoard information, be transparent &
        push it out there for others to use.
        Demonstrate personal vulnerability; let
        people get to know you. "
    },
    {...}
]

```

Comments

Comments are nested within the post they correspond to (both in the route and in their post's json)

List Comments for a Post

```
GET api/2/post/:post_id/comments
```

Description

If the post has comments returns an Array of Objects otherwise returns an empty Array.

Returned Object Properties

Each element in the returned array is an object with these properties

key	value	notes
id	string	id of the comment
message	string	
parent	string	id of parent post
hidden	boolean	
from	object	see user profile show

Examples

REQUEST

```
GET api/2/posts/530f62bf6c7db94242010052/comments
```

RESPONSE

```
[
  {
    "id": "530f62bf6c7db94242010052",
    "message" : "dang, I feel like a celebrity with all this
recognition!!",
    "hidden" : false,
    "parent" : "53626b371383542ef500000f",
    "from": {
      "id": "52e9e37f549d52e7a10000cb",
```

```
"first_name": "Angela",
"last_name": "Kimberly",
"profile_email": "test@youearnedit.com",
"login_email": "otheremail@youearnedit.com",
"status": "active",
"dob_day": null,
"dob_month": null,
"start_date": null,
"termination_date": null,
"reference_id": null,

"profile_pic":
"https://yei-production-images.s3.amazonaws.com/uploads/user_profile/
image/52e9e37f549d52e7a10000cb/medium_130305597728281127.jpg",

"profile_pic_small": "https://yei-production-images.s3.amazonaws.com/u
ploads/user_profile/image/52e9e37f549d52e7a10000cb/small_130305322808
1127.jpg",

"groups": [],

"giving_account": {
    "balance": 5425,
    "currency": "points",
    "conversion_rate": 1.0
},

"redemption_account": {
    "balance": 5052,
```

```

        "currency": "points",
        "conversion_rate": 1.0
    }
}
},
...
]

```

Comment Create

POST `api/2/posts/530f62bf6c7db94242010050/create_comment`

Description

Add a comment to an existing post.

NOTE: This method only makes sense in the context of an OAuth based session (ie, a logged in user). If Basic Auth is used to make this call, then the company “API” user will be used.

This will return the post object the new comment belongs to

Request Arguments

key	value	notes
comment	object	wrapper for all other properties

key	value	notes
message	string	

Returned Object Properties

key	value	notes
post	object	keys are shown below

key	value	notes
id	string	
points	integer	
type	string	
message	string	
hidden	boolean	
private	boolean	
from	object	see user_profile Show for properties
to	object	see user_profile Show for properties
comments	array of objects	New Comment will be the end element

Examples

REQUEST

POST api/2/posts/530f62bf6c7db94242010050/create_comment

```
{
  "comment": {
    "message": "This is a test comment"
  }
}
```

RESPONSE

```
{  
  
  "post": {  
  
    "id": "533f0f27ad72562af2000003",  
  
    "points": 94,  
  
    "type": "recognition",  
  
    "message": "hidididi",  
  
    "hidden": false,  
  
    "private": false,  
  
    "from": {  
  
      "id": "52e93230549d32e7a1000013",  
  
      "first_name": "test",  
  
      "last_name": "user",  
  
      "profile_email": "test@youearnedit.com",  
  
      "login_email": "otheremail@youearnedit.com",  
      "status": "active",  
      "dob_day": null,  
      "dob_month": null,  
      "start_date": null,  
      "termination_date": null,  
      "reference_id": null,  
  
    }  
  
  }  
}
```

```
"profile_pic": null,  
"profile_pic_small": null,  
"giving_account": {  
    "balance": 0,  
    "currency": "points",  
    "conversion_rate": 1  
},  
"redemption_account": {  
    "balance": 0,  
    "currency": "points",  
    "conversion_rate": 1  
},  
"groups": [],  
"following": []  
},  
"to": [  
    {  
        "id": "531a5ac36c7db99dbb000017",  
        "first_name": "John",  
        "last_name": "Tester",  
        "profile_email": "test@youearnedit.com",
```

```
"login_email": "otheremail@youearnedit.com",
"status": "active",
"dob_day": null,
"dob_month": null,
"start_date": null
"termination_date": null,
"reference_id": null,

"profile_pic": null,

"profile_pic_small": null,

"giving_account": {
    "balance": 10,
    "currency": "points",
    "conversion_rate": 1
},

"redemption_account": {
    "balance": 2724,
    "currency": "points",
    "conversion_rate": 1
},

"groups": [],

"following": []
}

],
```

```
"comments": [  
  {  
    "id": "534c3492ad72561b48000012",  
    "message": "This is a comment created by the runscope  
api tests",  
    "hidden": false,  
    "parent" : "53626b371383542ef500000f",  
    "from": {  
      "id": "52f03150549d520d47007f2b",  
      "first_name": "test",  
      "last_name": "test",  
      "profile_email": "test@youearnedit.com",  
      "login_email": "otheremail@youearnedit.com",  
      "status": "active",  
      "dob_day": null,  
      "dob_month": null,  
      "start_date": null,  
      "termination_date": null,  
      "reference_id": null,  
      "profile_pic": null,  
      "profile_pic_small": null,  
      "giving_account": {  
        "balance": 0,  

```

```
        "currency": "points",
        "conversion_rate": 1
    },
    "redemption_account": {
        "balance": 0,
        "currency": "points",
        "conversion_rate": 1
    },
    "groups": [],
    "following": []
}
},
{
    "id": "534c59baad72561717000002",
    "message": "This is a test comment",
    "hidden": false,
    "from": {
        "id": "52f07150549d520d47007f2b",
        "first_name": "jason",
        "last_name": "test",
        "profile_email": "test@youearnedit.com",
```

```
"login_email": "otheremail@youearnedit.com",
"status": "active",
"dob_day": null,
"dob_month": null,
"start_date": null
"termination_date": null,
"reference_id": null,

"profile_pic": null,

"profile_pic_small": null,

"giving_account": {
    "balance": 0,
    "currency": "points",
    "conversion_rate": 1
},

"redemption_account": {
    "balance": 0,
    "currency": "points",
    "conversion_rate": 1
},

"groups": [],

"following": []
}
},
```

```
{  
  
  "id": "534c5a62ad7256572900000a",  
  
  "message": "This is a test comment",  
  
  "hidden": false,  
  
  "from": {  
  
    "id": "52f07150549d520d47047f2b",  
  
    "first_name": "test",  
  
    "last_name": "test",  
  
    "email": "test@youearnedit.com",  
  
    "active": true,  
  
    "profile_pic": null,  
  
    "profile_pic_small": null,  
  
    "giving_account": {  
  
      "balance": 0,  
  
      "currency": "points",  
  
      "conversion_rate": 1  
  
    },  
  
    "redemption_account": {  
  
      "balance": 0,  
  
      "currency": "points",  
  
      "conversion_rate": 1  
  
    }  
  
  }  
  
}
```

```
    },  
    "groups": [],  
    "following": []  
  }  
},  
{  
  "id": "534c5a80ad72565729000012",  
  "message": "3 This is a test comment",  
  "hidden": false,  
  "from": {  
    "id": "52f07150549d520d47007f2b",  
    "first_name": "test",  
    "last_name": "test",  
    "email": "test@youearnedit.com",  
    "active": true,  
    "profile_pic": null,  
    "profile_pic_small": null,  
    "giving_account": {  
      "balance": 0,  
      "currency": "points",  
      "conversion_rate": 1
```

```
    },  
    "redemption_account": {  
        "balance": 0,  
        "currency": "points",  
        "conversion_rate": 1  
    },  
    "groups": [],  
    "following": []  
}  
},  
{  
    "id": "534c5a9dad7256572900001a",  
    "message": "4 This is a test comment",  
    "hidden": false,  
    "from": {  
        "id": "52f07150549d520d47007f2b",  
        "first_name": "yei",  
        "last_name": "API",  
        "profile_email": "test@youearnedit.com",  
        "login_email": "test@youearnedit.com",  
        "status": "active",  
        "dob_day": null,  
    },  
}
```

```
    "dob_month": null,  
    "start_date": null  
    "termination_date": null,  
    "reference_id": null,  
  
    "profile_pic": null,  
  
    "profile_pic_small": null,  
  
    "giving_account": {  
        "balance": 0,  
        "currency": "points",  
        "conversion_rate": 1  
    },  
  
    "redemption_account": {  
        "balance": 0,  
        "currency": "points",  
        "conversion_rate": 1  
    },  
  
    "groups": [],  
  
    "following": []  
    }  
},  
{
```

```
"id": "534c5c1aad7256ab04000022",
"message": "5This is a test comment",
"hidden": false,
"from": {
  "id": "52f07150549d520d47007f2b",
  "first_name": "test",
  "last_name": "test",
  "profile_email": "jdason@example.com",
  "login_email": "tdest@example.com",
  "dob_day": null,
  "dob_month": null,
  "start_date": null,
  "termination_date": null,
  "status": "active",
  "profile_pic": null,
  "profile_pic_small": null,
  "giving_account": {
    "balance": 0,
    "currency": "points",
    "conversion_rate": 1
  },
}
```

```
        "redemption_account": {  
            "balance": 0,  
            "currency": "points",  
            "conversion_rate": 1  
        },  
        "groups": [],  
        "following": []  
    }  
}  
]  
}
```

Comment Update

```
PUT /api/2/posts/{POST_ID}/update_comment/{COMMENT_ID}
```

Description

Update an existing comment on a post.

Request Arguments

key	value	notes
comment	object	wrapper for all other properties

key	value	notes
message	string	

Returned Object Properties

None

Examples

REQUEST

PUT

/api/2/posts/530f62bf6c7db94242010050/update_comment/530f62bf6c7db9424201aa20

```
{
  "comment": {
    "message": "This is a comment"
  }
}
```

RESPONSE

200 OK

Comment Delete

```
DELETE /api/2/posts/{POST_ID}/delete_comment/{COMMENT_ID}
```

Description

Delete a comment from an existing post.

NOTE: This method only makes sense in the context of an OAuth based session (ie, a logged in user). If Basic Auth is used to make this call, then the company “API” user will be used.

Request Arguments

None

Returned Object Properties

None

Examples

REQUEST

DELETE

```
api/2/posts/530f62bf6c7db94242010050/delete_comment/530f62bf6c7db9424  
201aa20
```

RESPONSE

200 OK

Following

```
GET /api/2/user_profiles/{USER_PROFILE_ID}/toggle_follow
```

Description

Toggle the user following status from the current signed in user to the target user.

Returned Object Properties

none

Examples

REQUEST

```
GET /api/2/user_profiles/52e9e377549d52e7a1000055/toggle_follow
```

RESPONSE

200 OK

Notifications

Index

```
GET /api/2/notifications
```

Description

Get active notifications

Returned Object Properties

Returns an Array of Objects with the following properties,

key	value	notes
id	string	
type	string	can be: "receives_points", "comment", "cancel_award", "approve_redemption", "disapprove_redemption", "complete_redemption", "following_sends", "following_receives", "following_redeems", "adjust_giving_points", "adjust_redemption_points", "set_points"
message	string	

Examples

REQUEST

```
GET /api/2/notifications
```

RESPONSE (truncated)

```
[
  {
    id: "532863bd6c7db9692e0000e9",
    type: "following_sends",
    message: "Amanda Kimmerly sent recognition to Candace Carlisle"
  },
  {
    id: "5328634d6c7db9692e0000d5",
    type: "following_sends",
    message: "Amanda Kimmerly sent recognition to Tim Ryan"
  }
]
```

```

    },
    {
      id: "532862d105fd071045000194",
      type: "following_sends",
      message: "Amanda Kimmerly sent recognition to Nathan
        Lowery"
    },
    {
      id: "5328626b05fd078fac000070",
      type: "following_sends",
      message: "Amanda Kimmerly sent recognition to Kim
        Lowery"
    },
    {
      id: "532861756c7db93caf0001b9",
      type: "following_sends",
      message: "Amanda Kimmerly sent recognition to Mike
        McCown"
    }
  ]

```

Dismiss

POST /api/2/notifications/{ID}/dismiss

Description

Mark active notification as seen

Examples

REQUEST

POST /api/2/notifications/532863bd6c7db9692e0000e9/dismiss

RESPONSE

200 OK

Clear

POST /api/2/notifications/clear

Description

Mark all active notifications as seen

Examples

REQUEST

POST /api/2/notifications/clear

RESPONSE

200 OK

Stats

GET api/2/stats

Description

Summary statistics from the prior 30-day period.

Returned Object Properties

Each element in the returned array is an object with these properties

key	value	notes
-----	-------	-------

points_given	hash	total points sent to others past 30 days
points_redeemed	hash	total points redeemed for rewards past 30 days
available_to_give	hash	sum of active users giving points as of today
available_to_redeem	hash	sum of active users redemption points today
points_given_data	array	for charting purposes
points_redeemed_data	array	for charting purposes
top_givers	hash	by user_profile, top counts of sent recognition
top_receivers	hash	by user_profile, top counts of received recognition
tags	hash	count and users receiving this tag in past 30 days

Examples

REQUEST

```
GET api/2/stats
```

RESPONSE

```
{
  "points_given": {
    "count": 62,
    "total": 12846
  },
  "points_redeemed": {
    "count": 15,
    "total": 29500
  },
  "available_to_give": {
```

```
        count: 21,
        total: 125150
    },
    available_to_redeem:
    {
        count: 21,
        total: 118934
    },
    points_given_data:
    [
        {
            name: "17-Mar (Mon)<br/>350 points",
            x: 1395014400000,
            y: 2,
            date: "2014-03-17T00:00:00+00:00",
            posts: 2
        },
        ... truncated
        {
            name: "14-Apr (Mon)<br/>250 points",
            x: 1397433600000,
            y: 1,
            date: "2014-04-14T00:00:00+00:00",
            posts: 1
        }
    ],
    points_redeemed_data:
    [
        {
            name: "17-Mar (Mon)<br/>14000 points",
            x: 1395014400000,
            y: 3,
            date: "2014-03-17T00:00:00+00:00",
            posts: 3
        },
        {
```

```

        name: "18-Mar (Tue)<br/>3000 points",
        x: 1395100800000,
        y: 2,
        date: "2014-03-18T00:00:00+00:00",
        posts: 2
    },
    ...truncated
    {
        name: "08-Apr (Tue)<br/>500 points",
        x: 1396915200000,
        y: 1,
        date: "2014-04-08T00:00:00+00:00",
        posts: 1
    }
],
top_givers:
{
    52e9e346549d52e2a10000a3:
    {
        name: "Heath Padgett",
        first_name: "Heath",
        last_name: "Padgett",
        group: "",
        count: 16,
        total: 3400
    },
    52e9e37f549d52e7a10000cb:
    {
        name: "Amanda Kimmerly",
        first_name: "Amanda",
        last_name: "Kimmerly",
        group: "",
        count: 9,
        total: 2333
    },
    ...truncated

```

```
52e9e2eb549d52e7a1000067:
{
    name: "Mike McCown",
    first_name: "Mike",
    last_name: "McCown",
    group: "Engineering Team",
    count: 1,
    total: 250
}
},
top_receivers:
{
    52e9e35b549d52e7a10000b2:
    {
        name: "Jo Francis",
        first_name: "Jo",
        last_name: "Francis",
        group: "",
        count: 8,
        total: 1277
    },
    52e9e3c6549d52e7a1000102:
    {
        name: "Chelsey Graber",
        first_name: "Chelsey",
        last_name: "Graber",
        group: "Sales Team",
        count: 6,
        total: 2050
    },
    ...truncated
    52e9e37f549d52e7a10000cb:
    {
        name: "Amanda Kimmerly",
        first_name: "Amanda",
        last_name: "Kimmerly",
```

```
        group: "",
        count: 1,
        total: 250
    }
},
tags:
{
    52e9e22f549d52e7a100000f:
    {
        name: "Create Happiness",
        count: 17,
        type: "PreferredTag",
        list:
        {
            52e9e377549d52e7a10000c6:
            {
                id:
                "52e9e377549d52e7a10000c6"
                ,
                name: "Tim Ryan",
                image_url:
                "https://yei-production-images.s3.amazonaws.com/uploads/user\_profile/image/52e9e377549d52e7a10000c6/small\_130335881910511799.jpg",
                count: 18
            },
            52e9e35b549d52e7a10000b2:
            {
                id:
                "52e9e35b549d52e7a10000b2"
                ,
                name: "Jo Francis",
                image_url:
                "
```

```

    ages.s3.amazonaws.com/uploads/user_profile/image/52e9e35b549d52e7a10000b2/small_130290023363623862.jpg",
    count: 11
  },
  ...truncated
533060be6c7db96e8200018b:
{
  id:
    "533060be6c7db96e8200018b"
  ,
  name: "Nathan Walker",
  image_url:
    "https://vei-production-images.s3.amazonaws.com/uploads/user_profile/image/533060be6c7db96e8200018b/small_mini_magick20140324-5324-d2rno9.jpg","
  count: 3
}
}
},
52e9e22f549d52e7a100000d:
{
  name: "Open Book",
  count: 2,
  type: "PreferredTag",
  list:
  {
    530a5ac36c7db99dbb000017:
    {
      id:
        "530a5ac36c7db99dbb000017"
      ,

```

```

        name: "Fremen Deruvo",
        image_url:
        "https://yei-production-images.s3.amazonaws.com/uploads/user_profile/image/530a5ac36c7db99dbb000017/small_mini_magick20140228-2736-12mta9g.jpg",
        count: 4
    },
    52e9e387549d52e7a10000d0:
    {
        id:
        "52e9e387549d52e7a10000d0"
        ,
        name: "Tara Sinclair",
        image_url:
        "https://yei-production-images.s3.amazonaws.com/uploads/user_profile/image/52e9e387549d52e7a10000d0/small_mini_magick20140305-18244-1mznbw8.jpg",
        count: 2
    }
}
},
534c5404d00fb983d8000004:
{
    name: "user tag",
    count: 1,
    type: "Tag",
    list:
    {
        52e9e367549d52e7a10000bc:
        {

```


key	value	notes
device_token	string	required. Primary key for push notifications. (Apple generated identifier for push notifications. Value generated by Parse for android devices)
device_type	string	(optional). "ios" or "android" are the only two allowed values.
installation_id	string	(optional) Parse generated Id for android devices. Optional for iOS.

Examples

REQUEST

```
POST /api/2/register_push
```

```
{device_token:
"b92c1343ceb658ab17ab91a81c8e2911c121a07ef78eb88d992d05ddb627e889",
installation_id: "c0da8fc1-30f5-4f1c-b12c-317c518192f9", device_type:
"android" }
```

RESPONSE

```
200 OK
```

Sample Endpoints for mobile

Mobile device vendors should first login the mobile user via the OAuth2 mechanism detailed in this document. Once an Oauth token is acquired associated with the logged in user, the following api calls can be used.

Forgot Password	POST	/users/password?user[email]=(useremail)	either use webview, or can post directly to this URL without being authenticated.
-----------------	------	---	---

User Profile	GET	/api/2/user_profiles/{USER_PROFILE_ID}	
User search (with pagination)	GET	/api/2/user_profiles?search=(searchterm)	
Notifications	GET	/api/2/notifications	
Get Tags	GET	/api/2/tags	
Add Activity	POST	/api/2/recognition	Initial comps showed multiple tags allowed. Current design is to allow only 0..1 PreferredTag and 0..1 user defined tag.
Activity Feed (with pagination)	GET	/api/2/posts	
Follow User	GET	/api/2/user_profiles/{USER_PROFILE_ID}/toggle_follow	
UnFollow User	GET	/api/2/user_profiles/{USER_PROFILE_ID}/toggle_follow	
User Details	GET	/api/2/user_profiles/{USER_PROFILE_ID}	
Post Detail	GET	/api/2/posts/{POST_ID}	
Redemptions	GET	/api/2/redemption	
Approve Redemption	POST	/api/2/process_redemption/approve/{ITEM_ORDER_ID}	
Deny Redemption	POST	/api/2/process_redemption/deny/{ITEM_ORDER_ID}	

Create Comments	POST	/api/2/post/{POST_ID}/create_comment	
Delete Comment	DELETE	/api/2/post/{POST_ID}/comments_delete/{COMMENT_ID}	
Get Comment	GET	/api/2/post/{POST_ID}/comments	
Rewards	GET	/api/2/rewards	
Admin - Top Receivers	GET	/api/2/stats	